


**PCB LAYOUT**  
(Top View)



**SPECIFICATION :**


**1. Electrical Char.**

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC
- Dielectric Voltage : 1,000 RMS 60 Sec. Min.

**2. Physical Char.**

- Housing : PBT Glass Filled (UL 94V-0)
- Color : Black/Medium Gray Color
- Spring Wire : 0.45mm Dia. Phosphor Bronze  
Gold Plating Over Nickel
- Temperature Range : - 25 +90 C
- Durability : 500 Mating cycles Min.

**HC-011-4-A-X**



**HO CHIEN**  
www.hochien.com

TITLE  
LOW PROFILE FLANGE PCB JACK  
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR  
HC-011-4-A-X

SCALE SIZE DWG. NO. 9613 SERIES

DO NOT SECALE DRAWING	TOLERANCES UNLESS OTHERWISE NOTED	INCH	MM	DR.	DATA
 THIRD ANGLE PROJECTION	LINEAR $\frac{MM}{INCH}$	00±0.01	00±0.25	Steven	JUL-30 '04
		000±0.005	000±0.13	Johnn	JUL-30 '04
	ANGLE +0°30'	RADIL	+0.45 -0.15	APP'D Billy	JUL-30 '04

DWG. NO.  
**AS011001**