


**PCB LAYOUT
(Top View)**



SPECIFICATION :


1. Electrical Char.

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC.
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

- Housing : PBT Glass Filled (UL 94V-0)
- Color : Black Color
- Spring Wire : 0.38mm Thickness Phosphor Bronze
Gold Plating Over Nickel.
- Temperature Range : - 25 /+80 Deg C
- Durability : 500 Mating cycles Min.

HC-022-6-X-X



HO CHIEN

www.hochien.com

TITLE

LOW PROFILE PCB MOUNT SIDE ENTRY JACK
UL & cUL FILE NO. E151820

MODULAR JACKS ASSY FOR
HC-022-6-X-X

SCALE SIZE DWG. NO. 9682 SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTED	INCH	MM	DR. Steven	DATE JAN-12 '05
THIRD ANGLE PROJECTION	LINEAR MM FRACTIONS	DECIMALS 0.0005/0.001	0.0125 0.0254/0.13 0.0025/0.05	CHK'D Johnn	JAN-12 '05
MM INCH	ANGLE 1/32"	RADIAL	+0.08 -0.15	APP'D Billy	JAN-12 '05

DWG. NO. **AS022002**