

**PCB LAYOUT**  
(Top View)

**SPECIFICATION :**


**1. Electrical Char.**

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC.
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

**2. Physical char. RoHs Compliant**

- Housing : Nylon (UL 94V-0)
- Color : Black Color
- Spring Wire : 0.35mm Thickness Phosphor Bronze  
Gold Plating Over Nickel
- Temperature Range : - 25 /+90 Deg C
- Durability : 500 Mating cycles Min.

**HC-111SH-2-FXB4N7**



**HO CHIEN**

www.hochien.com

**TITLE**

RJ45 Side Entry Shielded Ganged Jack  
UL & cUL FILE NO.131820

**MODULAR JACKS ASSY FOR  
HC-111SH-2-FXB4N7**

SCALE SIZE DWG. NO. 9811 SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
 THIRD ANGLE PROJECTION	LINEAR	MM INCH	00±0.01 000±0.005 0000±0.002	00±0.25 000±0.13 0000±0.05	Steven AUG-16 '04
	ANGLE+0'30'	RADIL	+0.45 -0.15	CK'D Johnn AUG-16 '04	APP'D Billy AUG-16 '04

DWG. NO.

**AS111003**