


PCB LAYOUT



SPECIFICATION :

1. Electrical Char.

Insulation Resistance : 500M-ohm min.
 Contact Resistance : 20milli-ohm max.

Rating Current : 1.5A Max.
 Rating Voltage : 120VAC

Dielectric Voltage : 1000 RMS 60sec min.

2. Physical Char.

Housing : PBT 20% Glass Filled (UL 94V-0)

Color : Black Color

Spring Wire : 0.45mm Dia. Phosphor Bronze

Gold Plating Over Nickel

Temperature Range : - 25 +90 C

Durability : 500 cycle min.

HC-012-6-X-X

B=6p2c , C=6p4c
 D=6p6c

Gold plated
 1=15u, 3=50u
 2=30u, 4=6u

HO CHIEN

TITLE

RJ11 or RJ12 TOP ENTRY PCB JACK
 UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
 HC-012-6-X-X

SCALE SIZE DWG. NO. 9607 SERIES

DO NOT SCALE DRAWING	TOLERANCES UNLESS OTHERWISE NOTED	DNCH	MN	Steve	MAR-31 '03
THIRD ANGLE PROJECTION	LINEAR	MN - 0.001 - 0.005 DNCH - 0.001 - 0.005	MN - 0.001 - 0.005 DNCH - 0.001 - 0.005	John	MAR-31 '03
MN (INCH)	ANGLE +0.50°	RADII	+0.13 -0.13	Billy	MAR-31 '03

DWG. NO.
 AS012003