



PCB LAYOUT
(Top View)

SPECIFICATION :

1. Electrical Char.

- Insulation Resistance : 500M-Ohm Min.
 Contact Resistance : 20milli-Ohm Max.
 Rating Current : 1.5A Max.
 Rating Voltage : 120V AC.
 Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

- Housing : PBT Glass Filled (UL 94V-0)
 Color : Black / Medium Gray Color
 Spring Wire : 0.45mm Dia. Phosphor bronze
 Gold Plating Over Nickel
 Temperature Range : - 40°C / +85°C
 Durability : 500 Mating cycles Min.

HC-026-18-2-F-X

Number Of Ports

F=8p8c

Gold plated
 1=15u, 3=50u
 2=30u, 4= 6 u

HO CHIEN

www.hochien.com

TITLE

1x2 8 Positions
 MINI LOW PROFILE GANG JACK
 UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
 HC-026-18-2-F-LX

SCALE SIZE DWG. NO. 9660 SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE	
 THIRD ANGLE PROJECTION	LINEAR	MM INCH	00±0.01 000±0.005 0000±0.002	00±0.25 000±0.13 0000±0.05	<i>Steven</i> CK'D <i>Johnn</i> APP'D <i>Billy</i>	MAR-01 '06
	ANGLE	°0'30"	RADIAL	+0.45 -0.15		MAR-01 '06
	MM INCH					

DWG. NO.

AS026017-2