


**PCB LAYOUT**  
( Top View )



**SPECIFICATION :**

**1. Electrical Char.**

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC.
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

**2. Physical char.**

- Housing : PBT Glass Filled (UL 94V-0)
- Color : Black Color
- Spring Wire : 0.45mm Dia. Phosphor bronze  
Gold Plating Over Nickel
- Temperature Range : - 25 /+90 Deg C
- Durability : 500 Mating cycles Min.

**HC-032SH 8 F X A1 N1**



**HO CHIEN**  
[www.hochien.com](http://www.hochien.com)

TITLE  
RJ45 SIDE ENTRY SHIELDED PCB JACK  
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR  
HC-032SH 8 F X A1 N1

SCALE SIZE DWG. NO. 9632-S SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE		INCH	MM	DR. <b>Steven</b>	DATE JAN-12 '05
	LINEAR	MM INCH				
THIRD ANGLE PROJECTION	0.00±0.01	0.00±0.25	0.00±0.01	0.00±0.13	CK'D <b>Johnn</b>	JAN-12 '05
	0.000±0.005	0.000±0.05				
MM INCH	ANGLE +0°30'		RADIL	+0.45 -0.15	APP'D <b>Billy</b>	JAN-12 '05