



SPECIFICATION :

1. Electrical Char.

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC.
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

- Housing : PBT Glass Filled (UL 94V-0)
- Color : Black Color
- Spring Wire : 0.45mm Dia. Phosphor bronze
Gold Plating Over Nickel
- Temperature Range : - 25 /+90 Deg C
- Durability : 500 Mating cycles Min.

HC-040SH 8 F X A2 N1

NUMBER OF PORT

F=8P8C

Gold plated
1=15u , 3=50u
2=30u , 4=6u

Rohs Compliant

HO CHIEN
www.hochien.com

TITLE
1x8 8POSITIONS
SIDE ENTRY SHIELDED PCB GANG JACK
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
HC-040SH 8 F X A2 N1

SCALE SIZE DWG. NO. 9638-S SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
 THIRD ANGLE PROJECTION	LINEAR	MM INCH	00±0.01 00±0.005 000±0.02	Steven CK'D	SEP-24 '04
	ANGLE +0°30'	RADIAL	+0.45 -0.15	Johnn APP'D	SEP-24 '04
				Billy	SEP-24 '04

DWG. NO.

AS040027