



PCB LAYOUT  
(Top View)

## SPECIFICATION :

### 1. Electrical Char.

- Insulation Resistance : 500M-Ohm Min.  
 Contact Resistance : 20milli-Ohm Max.  
 Rating Current : 1.5A Max.  
 Rating Voltage : 120V AC.  
 Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

### 2. Physical char. RoHs Compliant

- Housing : PBT Glass Filled (UL 94V-0)  
 Color : Black Color  
 Spring Wire : 0.35mm Thickness Phosphor Bronze  
 Gold Plating Over Nickel.  
 Temperature Range : - 40°C / +85°C  
 Durability : 500 Mating cycles Min.

## HC-600-24-F-LX-D

F=8p8c

Gold plated  
 1=15u, 3=50u  
 2=30u, 4= 6 u

# HO CHIEN

www.hochien.com

TITLE

DOUBLE DECK GANG PCB JACK  
 UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR  
 HC-600-24-F-LX-D

SCALE SIZE DWG. NO.9600 SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
 THIRD ANGLE PROJECTION	LINEAR $\frac{MM}{INCH}$	00±0.01	00±0.25	Steven	JUN-22 '06
		000±0.005	000±0.13	CK'D	
	ANGLE ±0°30'	RADIL	+0.45 -0.15	John	JUN-22 '06
MM INCH				APP'D Billy	JUN-22 '06

DWG. NO.

AS600016-1