

**LEAD LENGTH :**

White And Red With 190±5 mm, The ends withnT/S 7±1mm.
Blue And Brown With 70±5 mm, The ends withnT/S 5±1mm.

SPECIFICATION :**1. Electrical Char.**

Insulation Resistance : 500milli-Ohm Min.
Contact Resistance : 20milli-Ohm Max.
Rating Current : 1.5A Max.
Delectric Voltage : 1,000 RMS 60 Sec. Min.

2. Physical Char.

Housing : ABS Resin (UL 94V-0)
Color : Grey Color
Contact Wires : 0.45mm Dia. Phosphor bronze
nickel plated and with 6u gold plated
Temperature Range : - 25 +85 C
Durability : 500 Mating cycles Min.
Wires : UL-1061 26AWG.

HO CHIEN
www.hochien.com

TITLE

HAND SET JACK CONNECTORS

UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
616W-A-4-190-70-ST

SCALE SIZE DWG. NO. 9906 SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
 THIRD ANGLE PROJECTION	LINEAR $\frac{MM}{INCH}$	00±0.01	00±0.25	Steven	JUN-29 '06
		000±0.005	000±0.13	CK D	JUN-29 '06
$\frac{MM}{INCH}$	ANGLE +0° 30'	0000±0.002	0000±0.05	John	JUN-29 '06
			+0.45 -0.15	APP D Billy	JUN-29 '06

DWG. NO.

AS616W005-1