

PCB LAYOUT
(Top View)

SPECIFICATION :


1. Electrical Char.

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC.
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

- Housing : PBT Glass Filled (UL 94V-0)
- Color : Black Color
- Spring Wire : 0.35mm Thickness Phosphor Bronze With Hard Gold Plated In Contact Area And Gold Flash In Solder Area Over Nickel Plated.
- Temperature Range : - 40°C / +85°C
- Soldering Temperature : 260°C For 5~10 Sec Max.
- Durability : 500 Mating cycles Min.

HC-004-8-F-LX



HO CHIEN www.hochien.com	
TITLE RJ45 SIDE ENTRY PCB JACK UL & cUL FILE NO. E131820	
MODULAR JACKS ASSY FOR HC-004-8-F-LX	
SCALE SIZE DWG. NO.9658 SERIES	

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR. <i>Steven</i>	DATE FEB-27 '07
THIRD ANGLE PROJECTION	LINEAR MM INCH	00±0.01 000±0.005 0000±0.002	00±0.25 000±0.13 0000±0.05	CK'D <i>Johnn</i>	FEB-27 '07
	ANGLE +0°30'	RADIL	+0.45 -0.15	APP'D <i>Billy</i>	FEB-27 '07