



| | | |
|---|-----------------|-----|
| 6 | DIELECTRIC | ABS |
| 5 | CRIMPING PATCH | Cu |
| 4 | SOLDERING PATCH | Cu |
| 3 | SHELL | ABS |
| 2 | BODY | Cu |
| 1 | DIELECTRIC | POM |

| TOLERANCE | | SIGNATURES | DATE |
|-------------|------------|------------------|----------|
| 0 - 10 | ± 0.05 | DRAFT: HuGongXue | 07.08.24 |
| 10 - 30 | ± 0.1 | CHECKED: | |
| 30 - 100 | ± 0.15 | | |
| 100 - 300 | ± 0.2 | | |
| 300 - 1000 | ± 0.3 | | |
| 1000 - 3000 | ± 0.5 | | |

| | |
|---|--|
| HO CHIEN <i>www.hochien.com</i> | |
|---|--|

| REV | PART NO. & SAMPLE NO. | DATE | BY |
|-----|-----------------------|------|----|
| A | JR-1812 | | |
| B | | | |

| APPROVAL: | | SCALE | UNIT | REV |
|-----------|--|-------|------|--------|
| SHEET | | 1:1 | mm | ϕ |
| OF | | | | |

| | |
|----------|-----------------------|
| TITLE | DC Plug 2.1X5.5X9.5mm |
| CUSTOMER | |